

View Online at <https://aerobasegroup.com/nsn/4720-01-262-2161>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 0.844 inches and 0.906 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

Between 1.125 inches and 1.188 inches

**Minimum Inside Bending Radius:**

5.500 inches

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Thread Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

3000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

750.0 pounds per square inch

**Thread Size:**

1.312 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

1500.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

7.875 inches working and 8.125 inches working

**Media For Which Designed:**

Fuel/oil, hydrocarbon and oil, lubricating, diester base single response

**Thread Series Designator:**

Unj 1st end

**Specification Data:**

81349-mil-h-83796/1 government specification

**Specification Or Standard:**

16 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0