## NSN 4720-01-262-2574

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.562 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-262-2574

Tempurature Rating:				
-67.0 degrees fahrenheit single response and 158.0 degrees fahrenheit single response				
Outside Diameter:				
0.797 inches				
Minimum Inside Bending Radius:				
2.000 inches				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
14 1st end				
Burst Test Pressure:				
1000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided steel wire				
Maximum Operating Pressure:				
205.0 pounds per square inch				
Thread Size:				
1.000 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
300.0 pounds per square inch				
Outer Covering Environmental Protection:				
Fire resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
26.000 inches working				
Media For Which Designed:				
Air single response and fuel/oil, hydrocarbon single response				

## NSN 4720-01-262-2574

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
ı	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	000	igilatoi.

Uns 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0