NSN 4720-01-262-3179

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-262-3179

| Round |
|---|
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 1.000 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.500 inches |
| Minimum Inside Bending Radius: |
| 12.000 inches |
| Exterior Color: |
| Gray |
| End Application: |
| 3810-01-165-0647 |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Complete fitting steel all ends |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Second End Relationship With First End: |
| Identical |
| Burst Test Pressure: |
| 16000.0 pounds per square inch |
| First End Swivel Action Capability: |
| Not included |
| Layer Composition And Location: |
| 1st layer spirally wrapped corrosion resistant steel fabric err-100 |
| Maximum Operating Pressure: |
| 4000.0 pounds per square inch |
| Thread Size: |
| 1.312 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |

NSN 4720-01-262-3179

Nonmetallic Hose Assembly - Page 2 of 2



| Hydrostatic Test Pressure: |
|---|
| 8000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Oil resistant and weatherproof |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 42.000 inches |
| Special Features: |
| Inner conveying tube material-rubber, synthetic |
| Media For Which Designed: |
| Hydraulic fluid single response |
| Thread Series Designator: |
| Un 1st end |
| Specification Or Standard: |
| 16 size |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A542a0