NSN 4720-01-262-3179

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-262-3179

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
1.500 inches
Minimum Inside Bending Radius:
12.000 inches
Exterior Color:
Gray
End Application:
3810-01-165-0647
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
16000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer spirally wrapped corrosion resistant steel fabric err-100
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end

NSN 4720-01-262-3179

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
8000.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
42.000 inches
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Un 1st end
Specification Or Standard:
16 size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0