Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-263-5678

Cross Sectional Sh	ape:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
Between 0.500 inche	es and 0.539 inches
Tempurature Rating	g:
-54.0 degrees celsiu	s and 121.0 degrees celsius single response
Outside Diameter:	
Between 0.898 inche	es and 0.945 inches
Minimum Inside Be	nding Radius:
5.500 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut flare 2nd	end
End Connection De	sign:
Straight 1st end	
Connection Type:	
Threaded internal tu	be 1st end
Features Provided:	
Reusable end fitting	6
Burst Test Pressur	e:
7000.0 pounds per s	quare inch
Layer Composition	And Location:
1st layer braided cot	ton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operatin	g Pressure:
1750.0 pounds per s	quare inch
Thread Size:	
0.875 inches 2nd en	t de la constante de
Seat Angle:	
37.0 degrees 2nd en	d
Hydrostatic Test Pr	essure:
3500.0 pounds per s	quare inch
Flow Angle:	
90.0 degrees 2nd en	d
Outer Covering Env	vironmental Protection:
Oil resistant	
Inside Surface Con	dition:
Smooth	



Measuring Method And Length:

99.000 inches working and 101.000 inches working

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0