## NSN 4720-01-264-8398

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-264-8398

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.380 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.680 inches
Minimum Inside Bending Radius:
3.500 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:

Smooth

**Measuring Method And Length:** 

136.000 inches

Media For Which Designed:

**Inside Surface Condition:** 

Fuel/oil, hydrocarbon single response

## NSN 4720-01-264-8398

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unf 2nd end
Specification Data:
81343-sae j517, 100r2 government standard
Specification Or Standard:
6 size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0