Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-265-7160

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.500 inches	
Tempurature Rating:	
40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response	
Dutside Diameter:	
0.970 inches	
Minimum Inside Bending Radius:	
7.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
14000.0 pounds per square inch	
_ayer Composition And Location:	
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded ru	ıbber, synthetic
Maximum Operating Pressure:	
4250.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
180.000 inches	
Thread Series Designator:	
Unf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 4720-01-265-7160

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

