NSN 4720-01-266-8164

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-266-8164

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.508 inches
Minimum Inside Bending Radius:
9.625 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
5000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
27.500 inches working
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Unjf 1st end
Specification Data:

96906-ms28762 government standard

NSN 4720-01-266-8164

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0