Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-266-8170

| New Online at https://defobasegroup.com/hsi//4720-01-200-0170         |
|---|
| Cross Sectional Shape:  |
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.310 inches  |
| Tempurature Rating:   |
| -15.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.670 inches  |
| Minimum Inside Bending Radius:  |
| 4.000 inches  |
| Exterior Color:   |
| Red   |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 2500.0 pounds per square inch   |
| Layer Composition And Location:                                       |
| 1st layer braided wire and outer layer braided textile yarn           |
| Maximum Operating Pressure:   |
| 350.0 pounds per square inch  |
| Thread Size:  |
| 0.500 inches 1st end  |
| Seat Angle:   |
| 45.0 degrees 1st end  |
| Vacuum In Torr:   |
| 50.8  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 122.250 inches  |
| Media For Which Designed:   |
| Refrigerant 12 single response  |
| Thread Series Designator:   |
| Unf 1st end   |

## NSN 4720-01-266-8170

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

