NSN 4720-01-267-0360

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-267-0360 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -15.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.920 inches **Minimum Inside Bending Radius:** 5.500 inches **Exterior Color:** Red **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 2500.0 pounds per square inch **Layer Composition And Location:** 1st layer braided wire and outer layer braided textile yarn **Maximum Operating Pressure:** 350.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 45.0 degrees 1st end **Vacuum In Torr:**

50.8 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 603.000 inches Media For Which Designed: Refrigerant 12 single response

NSN 4720-01-267-0360

Nonmetallic Hose Assembly - Page 2 of 2



Th.		Carias	Danie	
1111	reau	Series	Desig	mator.

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0