

View Online at <https://aerobasegroup.com/nsn/4720-01-268-7388>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.380 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.750 inches

Minimum Inside Bending Radius:

1.750 inches

Exterior Color:

Black

Connection Style:

Swivel, plain 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external pipe 2nd end

Features Provided:

Reusable end fittings

Burst Test Pressure:

900.0 pounds per square inch

Layer Composition And Location:

1st layer molded rubber, synthetic and 2nd layer braided textile yarn and 3rd layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

225.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Hydrostatic Test Pressure:

450.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

40.000 inches

Special Features:

One end fitting fixed and other ed swivel; finish with electrodeposited zinc with supplementary chromate treatment

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A542a0