

View Online at <https://aerobasegroup.com/nsn/4720-01-268-7388>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.380 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.750 inches

**Minimum Inside Bending Radius:**

1.750 inches

**Exterior Color:**

Black

**Connection Style:**

Swivel, plain 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded external pipe 2nd end

**Features Provided:**

Reusable end fittings

**Burst Test Pressure:**

900.0 pounds per square inch

**Layer Composition And Location:**

1st layer molded rubber, synthetic and 2nd layer braided textile yarn and 3rd layer braided textile yarn and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

225.0 pounds per square inch

**Thread Size:**

0.375 inches 1st end

**Hydrostatic Test Pressure:**

450.0 pounds per square inch

**Outer Covering Environmental Protection:**

Oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

40.000 inches

**Special Features:**

One end fitting fixed and other ed swivel; finish with electrodeposited zinc with supplementary chromate treatment

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Nptf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A542a0