## NSN 4720-01-268-7396

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-268-7396

Cross Sectional Shape:

Cross Sectional Snape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.469 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
18.500 inches
Thread Series Designator:

Unjf 1st end

## NSN 4720-01-268-7396

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data:
96906-ms8005 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Mil-std (military Standard):

Mil-h-25579 spec.

**Fiig:** A542a0