Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-268-7898

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.410 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.770 inches |
| Minimum Inside Bending Radius: |
| 4.620 inches |
| End Application: |
| 5865-01-236-4235 |
| Connection Style: |
| Gasket seal / optional end 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal boss 2nd end |
| Burst Test Pressure: |
| 1750.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided textile yarn and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 350.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 2nd end |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 25.000 inches |
| Thread Series Designator: |
| Unjf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 4720-01-268-7898

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

