Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-269-7906

cross Sectional Shape:	
Round	
hread Class:	
b 1st end	
'hread Direction:	
light-hand 1st end	
nside Diameter:	
.340 inches	
empurature Rating:	
40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response	
Dutside Diameter:	
.550 inches	
Iinimum Inside Bending Radius:	
.500 inches	
Connection Style:	
Swivel nut flare 2nd end	
Ind Connection Design:	
Straight 1st end	
Connection Type:	
hreaded internal tube 1st end	
eatures Provided:	
Reusable end fittings	
Burst Test Pressure:	
000.0 pounds per square inch	
ayer Composition And Location:	
st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant stee	wire
laximum Operating Pressure:	
000.0 pounds per square inch	
hread Size:	
.562 inches 2nd end	
Seat Angle:	
7.0 degrees 2nd end	
lydrostatic Test Pressure:	
000.0 pounds per square inch	
low Angle:	
5.0 degrees 2nd end	
Outer Covering Environmental Protection:	
ire resistant	
nside Surface Condition:	
Smooth	
leasuring Method And Length:	
2.875 inches	



Media For Which Designed: Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end
Specification Data:

81349-mil-h-83797 government specification

Specification Or Standard:

6 size

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0