## NSN 4720-01-269-7907

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-269-7907

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Tempurature Rating:	
-58.0 degrees fahrenheit and 158.0 degrees fahrenheit single response	
Outside Diameter:	
0.625 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
1000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided textile yarn and outer layer molded rubber, synthetic	
Maximum Operating Pressure:	
150.0 pounds per square inch	
Thread Size:	
0.562 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
300.0 pounds per square inch	
Outer Covering Environmental Protection:	
Abrasion resistant and fuel resistant and oil resistant	
Inside Surface Condition:	

Smooth

**Measuring Method And Length:** 

16.000 inches

**Special Features:** 

Nsn 4720-00-720-1096 (hose) should be cut to 16 in. Before attaching the adapters

**Media For Which Designed:** 

Alcohol, ethyl and oil, lubricating, diester base and water single response

## NSN 4720-01-269-7907

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	<b>Designator:</b>
--------	--------	--------------------

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0