Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-270-2503

-	
	ss Sectional Shape:
Rou	
	ead Class:
	Ist end
Thre	ead Direction:
Righ	nt-hand 1st end
Insi	de Diameter:
0.40)6 inches
Tem	npurature Rating:
-40.0	0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Out	side Diameter:
0.76	6 inches
Mini	imum Inside Bending Radius:
4.62	25 inches
Con	nection Style:
Swiv	vel nut flare 1st end
End	Connection Design:
Stra	ight 1st end
End	I Fitting Component And Material:
Com	nplete fitting steel all ends
Con	nection Type:
Thre	eaded internal tube 1st end
Feat	tures Provided:
Reu	sable end fittings
Sec	ond End Relationship With First End:
Iden	ntical
Bur	st Test Pressure:
800(0.0 pounds per square inch
Firs	t End Swivel Action Capability:
Not	included
Lay	er Composition And Location:
1st I	layer braided textile yarn err-100
Max	kimum Operating Pressure:
2000	0.0 pounds per square inch
Thre	ead Size:
0.75	50 inches 1st end
Sea	t Angle:
) degrees 1st end
	uum In Torr:
50.8	
	de Surface Condition:
	both

NSN 4720-01-270-2503

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 84.000 inches **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Hydraulic fluid single response **Thread Series Designator:** Unf 1st end Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0