NSN 4720-01-270-3270

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-270-3270

Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
1.240 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response	
Outside Diameter:	
1.542 inches	
Minimum Inside Bending Radius:	
6.250 inches	
Connection Style:	
Swivel nut, flareless 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Thready Qty Per Inch (tpi):	
12 2nd end	
Burst Test Pressure:	
3600.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
1000.0 pounds per square inch	
Thread Size:	
1.625 inches 2nd end	
Seat Angle:	
12.0 degrees 2nd end	
Hydrostatic Test Pressure:	
1800.0 pounds per square inch	
Flow Angle:	
90.0 degrees 2nd end	

Convoluted

Outer Covering Environmental Protection:

Age resistant and water resistant Inside Surface Condition:

NSN 4720-01-270-3270

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
22.500 inches
Thread Series Designator:
Unj 2nd end
Shelf Life:

Unit Of Measure:

Demilitarization:

No

Fiig:

N/a

. ...

A542a0