

View Online at <https://aerobasegroup.com/nsn/4720-01-270-3280>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.922 inches

Minimum Inside Bending Radius:

5.500 inches

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

7000.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and 2nd layer braided wire and 3rd layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

1750.0 pounds per square inch

Thread Size:

0.875 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Flow Angle:

90.0 degrees 1st end

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

23.750 inches

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0