## NSN 4720-01-270-5807

**Cross Sectional Shape:** 

Round

**Thread Class:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-270-5807

3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.240 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
1.542 inches
Minimum Inside Bending Radius:
6.250 inches
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
3600.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.625 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
1800.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:

Convoluted

Age resistant and water resistant

**Inside Surface Condition:** 

## NSN 4720-01-270-5807

Nonmetallic Hose Assembly - Page 2 of 2



<b>Measuring Method And Length:</b>
38.500 inches
Thread Series Designator:
Unj 2nd end
Shelf Life:
N/a
Unit Of Measure:

**Demilitarization:** No

Fiig:

A542a0