

View Online at <https://aerobasegroup.com/nsn/4720-01-270-5808>

Cross Sectional Shape:

Round

Inside Diameter:

1.125 inches

Tempurature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Flange Thickness:

0.315 inches 2nd end

Outside Diameter:

1.500 inches

Minimum Inside Bending Radius:

9.000 inches

Angle Between Rigid Elbow Fittings In Deg:

270.0

Center To Center Distance Between Bolt Holes Along Width:

1.190 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.310 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.120 inches 2nd end

Flange Width:

1.390 inches 2nd end

Connection Style:

Plain w/ gasket groove (sae flanged head) 2nd end

Bolt Hole Diameter:

0.469 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

2500.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and 2nd layer braided wire and 3rd layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

625.0 pounds per square inch

Hydrostatic Test Pressure:

1250.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.750 inches working

Flange Style:

Double oval (sae split type flange) 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0