Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-01-270-9611



Cross Sectional Shape:

Round

Inside Diameter:

1.812 inches

Tempurature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Flange Thickness:

0.375 inches 2nd end

Outside Diameter:

2.220 inches

Minimum Inside Bending Radius:

13.250 inches

Center To Center Distance Between Bolt Holes Along Width:

1.688 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

3.062 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

4.000 inches 2nd end

Flange Width:

3.720 inches 2nd end

Connection Style:

Plain w/ gasket groove (sae flanged head) 2nd end

Bolt Hole Diameter:

0.531 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

1400.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and 2nd layer braided wire and 3rd layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

350.0 pounds per square inch

Hydrostatic Test Pressure:

700.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition: Smooth Measuring Method And Length: 20.500 inches Flange Style: Double oval (sae split type flange) 1st end Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0