Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-273-0506

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
0.375 inches	
Tempurature Rating:	
40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.750 inches	
Minimum Inside Bending Radius:	
5.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
16000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer laye	r molded rubber,
chloroprene	
Maximum Operating Pressure:	
4000.0 pounds per square inch	
Thread Size:	
0.562 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
nside Surface Condition:	
Smooth	
Measuring Method And Length:	
40.000 inches	
Thread Series Designator:	
Jnjf 1st end	
Shelf Life:	
V/a	

N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0