NSN 4720-01-273-1054

Cross Sectional Shape:

Between 0.173 inches and 0.203 inches

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-273-1054

Tempurature Rating:			
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response			
Outside Diameter:			
Between 0.304 inches and 0.343 inches			
Minimum Inside Bending Radius:			
2.000 inches			
Exterior Color:			
Natural			
Connection Style:			
Swivel nut flare 2nd end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Burst Test Pressure:			
7000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
1500.0 pounds per square inch			
Thread Size:			
0.438 inches 1st end			
Seat Angle:			
37.0 degrees 2nd end			
Hydrostatic Test Pressure:			
3000.0 pounds per square inch			
Flow Angle:			
90.0 degrees 2nd end			
Outer Covering Environmental Protection:			
Corrosion resistant and fuel resistant			
Vacuum In Torr:			
50.8			
Inside Surface Condition:			
Smooth			

NSN 4720-01-273-1054

Nonmetallic Hose Assembly - Page 2 of 2



Measuring	Method	And	Length:

11.500 inches working

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0