## NSN 4720-01-273-1304

**Cross Sectional Shape:** 

**Inside Diameter:** 0.785 inches

**Tempurature Rating:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-273-1304

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Bolt Circle Diameter:
2.688 inches 1st end
Flange Thickness:
0.345 inches 1st end
Outside Diameter:
1.075 inches
Minimum Inside Bending Radius:
3.750 inches
Bolt Hole Quantity:
4 1st end
Flange Outside Diameter:
3.821 inches 1st end
Connection Style:
Raised 1st end
Bolt Hole Diameter:
0.562 inches 1st end
Raised Face Height:
0.113 inches 1st end
Raised Face Diameter:
1.750 inches 1st end
End Flames Constructions
End Flange Construction:
Solid 1st end
Solid 1st end
Solid 1st end  End Connection Design:
Solid 1st end  End Connection Design:  Straight 1st end
Solid 1st end  End Connection Design:  Straight 1st end  Connection Type:
Solid 1st end  End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end
Solid 1st end  End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Burst Test Pressure:
Solid 1st end  End Connection Design:  Straight 1st end  Connection Type:  Raised face flange 1st end  Burst Test Pressure:  3600.0 pounds per square inch
Solid 1st end  End Connection Design:  Straight 1st end  Connection Type:  Raised face flange 1st end  Burst Test Pressure:  3600.0 pounds per square inch  Layer Composition And Location:
Solid 1st end  End Connection Design:  Straight 1st end  Connection Type:  Raised face flange 1st end  Burst Test Pressure:  3600.0 pounds per square inch  Layer Composition And Location:  Outer layer braided corrosion resistant steel wire
Solid 1st end  End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Burst Test Pressure: 3600.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
Solid 1st end  End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Burst Test Pressure: 3600.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch
Solid 1st end  End Connection Design: Straight 1st end  Connection Type: Raised face flange 1st end  Burst Test Pressure: 3600.0 pounds per square inch  Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure: 1000.0 pounds per square inch  Hydrostatic Test Pressure:

## NSN 4720-01-273-1304

A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
28.000 inches
Flange Style:
Round w/ bolt holes 1st end
Special Features:
Two hose assemblies connected by 90 degrees elbow, first and second leg lg identical, 14.000 in. Lon
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: