
Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-274-0409

Cross Sectional Sh	ape:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.125 inches	
Tempurature Rating	j :
-65.0 degrees fahren	heit single response and 450.0 degrees fahrenheit single response
Outside Diameter:	
0.250 inches	
Minimum Inside Be	nding Radius:
2.000 inches	
Connection Style:	
Swivel nut flare 2nd e	and
End Connection De	sign:
Straight 1st end	
Connection Type:	
Threaded internal tub	be 1st end
Burst Test Pressure):
12000.0 pounds per	square inch
Layer Composition	And Location:
Outer layer braided o	corrosion resistant steel wire
Maximum Operating	g Pressure:
1500.0 pounds per s	quare inch
Thread Size:	
0.462 inches 2nd end	t
Seat Angle:	
37.0 degrees 2nd en	d
Flow Angle:	
90.0 degrees 2nd en	d
Inside Surface Con	dition:
Smooth	
Measuring Method	And Length:
53.250 inches	
Thread Series Desig	gnator:
Unf 2nd end	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 4720-01-274-0409

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

