4000.0 pounds per square inch

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-275-4193

	Sectional Shape:
Round	
Inside I	Diameter:
3.000 in	nches
Tempu	rature Rating:
-40.0 de	egrees fahrenheit and 200.0 degrees fahrenheit single response
Bolt Cir	rcle Diameter:
6.000 in	nches 1st end
Flange	Thickness:
0.500 in	nches 1st end
Outside	e Diameter:
3.594 in	nches
Minimu	ım Inside Bending Radius:
33.000	inches
Bolt Ho	ble Quantity:
4 1st en	nd
Flange	Outside Diameter:
7.500 ir	nches 1st end
Connec	ction Style:
Raised	1st end
Bolt Ho	ble Diameter:
0.750 ir	nches 1st end
Raised	Face Height:
0.062 ir	nches 1st end
Raised	Face Diameter:
4.500 ir	nches 1st end
End Fla	ange Construction:
Solid 1s	st end
End Co	onnection Design:
Straight	t 1st end
Connec	ction Type:
Raised	face flange 1st end
Feature	es Provided:
Reusab	ole end fittings
Burst T	Fest Pressure:
8000.0	pounds per square inch
Layer C	Composition And Location:
1st laye	er braided textile yarn and 2nd layer braided steel wire and 3rd layer braided textile yarn and outer layer molded rubber, synthetic
Maximu	um Operating Pressure:
2000.0	pounds per square inch
	static Test Pressure:

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:

Smooth

Measuring Method And Length:

13.500 inches

Flange Style:

Round w/ bolt holes 1st end

## Media For Which Designed:

Fuel/oil, hydrocarbon and water, fresh and water, salt single response

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0