NSN 4720-01-275-4194

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-275-4194 **Cross Sectional Shape:** Round **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.625 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 1.078 inches **Minimum Inside Bending Radius:** 2.750 inches **Exterior Color:** Blue **Connection Style:** External seat for gasket seal (boss) 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external boss 1st end **Features Provided:** Reusable end fittings Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 3000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 750.0 pounds per square inch **Thread Size:** 1.750 inches 1st end **Hydrostatic Test Pressure:** 1500.0 pounds per square inch **Outer Covering Environmental Protection:** Fire resistant **Inside Surface Condition:**

Smooth

Measuring Method And Length:

12.000 inches

NSN 4720-01-275-4194

Nonmetallic Hose Assembly - Page 2 of 2



	Media	For	Which	Design	ned:
--	-------	-----	-------	--------	------

Fuel/oil, hydrocarbon and hydraulic fluid, phosphate-ester base and water single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0