NSN 4720-01-275-4196

Cross Sectional Shape:

Inside Diameter: 2.375 inches

Tempurature Rating:

Bolt Circle Diameter: 4.750 inches 1st end Flange Thickness:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-275-4196

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

0.438 inches 1st end
Outside Diameter:
2.875 inches
Minimum Inside Bending Radius:
24.000 inches
Bolt Hole Quantity:
4 1st end
Flange Outside Diameter:
6.000 inches 1st end
Connection Style:
Raised 1st end
Bolt Hole Diameter:
0.750 inches 1st end
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:
3.281 inches 1st end
End Flange Construction:
Solid 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting copper alloy all ends
Connection Type:
Raised face flange 1st end
Features Provided:
Reusable end fittings
Second End Relationship With First End:
Identical
Burst Test Pressure:
4400.0
1400.0 pounds per square inch
First End Swivel Action Capability:

NSN 4720-01-275-4196

Nonmetallic Hose Assembly - Page 2 of 2



Layer Composition And Location: 1st layer braided textile yarn err-100 **Maximum Operating Pressure:** 350.0 pounds per square inch **Hydrostatic Test Pressure:** 700.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 18.000 inches Flange Style: Round w/ bolt holes 1st end **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A542a0