Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-276-4956

Cross Secti	onal Shape:
Round	
Thread Clas	s:
3b 1st end	
Thread Dire	ction:
Right-hand 1	st end
Inside Diam	eter:
0.204 inches	
Tempuratur	e Rating:
-65.0 degree	s fahrenheit and 300.0 degrees fahrenheit single response
Outside Dia	meter:
0.461 inches	
Minimum In	side Bending Radius:
2.000 inches	
Angle Betw	een Rigid Elbow Fittings In Deg:
180.0	
Connection	Style:
Swivel nut fla	are 1st end
End Conne	ction Design:
Elbow 1st er	ld
Connection	Туре:
Threaded in	ernal tube 1st end
Burst Test I	Pressure:
3000.0 poun	ds per square inch
Layer Comp	oosition And Location:
1st layer bra	ided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum C	perating Pressure:
1000.0 poun	ds per square inch
Thread Size	:
0.438 inches	1st end
Seat Angle:	
37.0 degree	s 1st end
Hydrostatic	Test Pressure:
3000.0 poun	ds per square inch
Flow Angle	
90.0 degree	s 1st end
Inside Surfa	ce Condition:
Smooth	
Measuring	Method And Length:
62.750 inche	es working
Media For V	Vhich Designed:
Fuel/oil, hyd	Irocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0