

View Online at <https://aerobasegroup.com/nsn/4720-01-276-5923>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.500 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

2.062 inches

Minimum Inside Bending Radius:

20.000 inches

End Application:

2320-01-205-2684

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

1.875 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon and water single response

Thread Series Designator:

Un 2nd end

Specification Data:

81349-mil-h-13531 government specification

Specification Or Standard:

1 type and a class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0