

View Online at <https://aerobasegroup.com/nsn/4720-01-276-5923>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.500 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

2.062 inches

**Minimum Inside Bending Radius:**

20.000 inches

**End Application:**

2320-01-205-2684

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 2nd end

**Burst Test Pressure:**

2000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

500.0 pounds per square inch

**Thread Size:**

1.875 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

1000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

17.000 inches

**Media For Which Designed:**

Fuel/oil, hydrocarbon and water single response

**Thread Series Designator:**

Un 2nd end

**Specification Data:**

81349-mil-h-13531 government specification

**Specification Or Standard:**

1 type and a class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0