

View Online at <https://aerobasegroup.com/nsn/4720-01-276-8660>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.844 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

1.465 inches

**Minimum Inside Bending Radius:**

5.500 inches

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 2nd end

**Burst Test Pressure:**

3000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

750.0 pounds per square inch

**Thread Size:**

1.312 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

1500.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

26.625 inches

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources; 00624 and 26512 have indicated their part number contained asbestos prior to 1984; they continue to manufacture the same part number without asbestos material after 1984

**Thread Series Designator:**

Unj 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0