NSN 4720-01-278-8665

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-278-8665

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.188 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response				
Outside Diameter:				
0.422 inches				
Minimum Inside Bending Radius:				
2.000 inches				
Connection Style:				
Swivel nut flare 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Reusable end fittings				
Burst Test Pressure:				
12000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided synthetic cord and outer layer molded rubber, synthetic				
Maximum Operating Pressure:				
3000.0 pounds per square inch				
Thread Size:				
0.438 inches 1st end				
Seat Angle:				
37.0 degrees 2nd end				
Hydrostatic Test Pressure:				
6000.0 pounds per square inch				
Flow Angle:				
90.0 degrees 2nd end				
Outer Covering Environmental Protection:				
Abrasion resistant and oil resistant and weatherproof				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				

92.000 inches

NSN 4720-01-278-8665

Nonmetallic Hose Assembly - Page 2 of 2



_	brood	Carias	Docionatori
ı	meau	oenes	Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0