Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-279-1407

Cross Sectional Sha	ape:
Round	
Thread Class:	
3b 2nd end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.355 inches	
Tempurature Rating	J:
-40.0 degrees fahren	heit and 400.0 degrees fahrenheit single response
Outside Diameter:	
0.560 inches	
Minimum Inside Be	nding Radius:
2.250 inches	
Connection Style:	
Swivel nut flare 2nd e	end
End Connection De	sign:
Straight 1st end	
Connection Type:	
Threaded internal tub	be 1st end
Burst Test Pressure	»:
4000.0 pounds per s	quare inch
Layer Composition	And Location:
1st layer braided cor	rosion resistant steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating	g Pressure:
1000.0 pounds per se	quare inch
Thread Size:	
0.562 inches 2nd end	t
Seat Angle:	
37.0 degrees 2nd en	d
Hydrostatic Test Pr	essure:
2000.0 pounds per s	quare inch
Flow Angle:	
45.0 degrees 2nd en	d
Vacuum In Torr:	
28.0	
Inside Surface Con	dition:
Convoluted	
Measuring Method	And Length:
24.000 inches	
Thread Series Desig	ynator:
Unjf 1st end	

NSN 4720-01-279-1407

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

