

View Online at <https://aerobasegroup.com/nsn/4720-01-279-5667>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.510 inches

Temperature Rating:

-54.0 degrees celsius single response and 204.0 degrees celsius single response

Outside Diameter:

1.800 inches

Minimum Inside Bending Radius:

7.500 inches

Connection Style:

Swivel nut, inverted flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

14 2nd end

Burst Test Pressure:

3000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

750.0 pounds per square inch

Thread Size:

1.843 inches 2nd end

Seat Angle:

8.5 degrees 2nd end

Hydrostatic Test Pressure:

1500.0 pounds per square inch

Flow Angle:

81.0 degrees 2nd end

Inside Surface Condition:

Convuluted

Measuring Method And Length:

13.375 inches working and 13.625 inches working

Special Features:

Firesleeve and dynatube/dual-seal fittings

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources, 00624 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Unjs 2nd end

Specification Data:

26512-gh511ge manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0