

View Online at <https://aerobasegroup.com/nsn/4720-01-279-5667>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.510 inches

**Temperature Rating:**

-54.0 degrees celsius single response and 204.0 degrees celsius single response

**Outside Diameter:**

1.800 inches

**Minimum Inside Bending Radius:**

7.500 inches

**Connection Style:**

Swivel nut, inverted flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

14 2nd end

**Burst Test Pressure:**

3000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

750.0 pounds per square inch

**Thread Size:**

1.843 inches 2nd end

**Seat Angle:**

8.5 degrees 2nd end

**Hydrostatic Test Pressure:**

1500.0 pounds per square inch

**Flow Angle:**

81.0 degrees 2nd end

**Inside Surface Condition:**

Convuluted

**Measuring Method And Length:**

13.375 inches working and 13.625 inches working

**Special Features:**

Firesleeve and dynatube/dual-seal fittings

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources, 00624 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

**Thread Series Designator:**

Unjs 2nd end

**Specification Data:**

26512-gh511ge manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0