## NSN 4720-01-279-8664

**Cross Sectional Shape:** 

Round

Thread Class: 3b 2nd end

**Thread Direction:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-279-8664

Right-hand 2nd end
Inside Diameter:
0.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response
Outside Diameter:
0.656 inches
Minimum Inside Bending Radius:
5.500 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 2nd end
Features Provided:
Reusable end fittings
Burst Test Pressure:
7000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.875 inches 2nd end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
11.500 inches working

## NSN 4720-01-279-8664

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

Made with firesleeve

**Thread Series Designator:** 

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0