NSN 4720-01-281-0994

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-281-0994

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
2.062 inches
Minimum Inside Bending Radius:
20.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
1.875 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
1000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
23.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 2nd end

NSN 4720-01-281-0994

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0