Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-281-5897

	ross Sectional Shape:
	ound
	hread Class:
	o 1st end
	nread Direction:
	ight-hand 1st end side Diameter:
-	250 inches
	empurature Rating:
	5.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
	utside Diameter:
-	550 inches
	inimum Inside Bending Radius:
	000 inches
Aı	ngle Between Rigid Elbow Fittings In Deg:
0.	0
С	onnection Style:
S١	wivel nut flare 1st end
Er	nd Connection Design:
EI	bow 1st end
C	onnection Type:
Tł	nreaded internal tube 1st end
B	urst Test Pressure:
35	50.0 pounds per square inch
M	aximum Operating Pressure:
10	00.0 pounds per square inch
Tł	nread Size:
0.	438 inches 1st end
Se	eat Angle:
37	7.0 degrees 1st end
H	ydrostatic Test Pressure:
20	00.0 pounds per square inch
FI	ow Angle:
45	5.0 degrees 1st end
In	side Surface Condition:
Sı	mooth
Μ	easuring Method And Length:
22	2.250 inches
Tł	nread Series Designator:
U	nf 1st end
SI	helf Life:
N/	/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0