## NSN 4720-01-281-5898

**Cross Sectional Shape:** 

Round

Smooth

**Thread Class:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-281-5898

| 3a 1st end  |
|---|
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.750 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 1.230 inches  |
| Minimum Inside Bending Radius:  |
| 9.500 inches  |
| Connection Style:   |
| External seat for gasket seal (boss) 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| End Fitting Component And Material:   |
| Complete fitting nickel alloy all ends  |
| Connection Type:  |
| Threaded external boss 1st end  |
| Features Provided:  |
| Reusable end fittings   |
| Thready Qty Per Inch (tpi):   |
| 12 1st end  |
| Second End Relationship With First End:   |
| Identical   |
| Burst Test Pressure:  |
| 12000.0 pounds per square inch  |
| First End Swivel Action Capability:   |
| Not included  |
| Layer Composition And Location:   |
| 1st layer braided textile yarn err-100  |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch   |
| Thread Size:  |
| 1.750 inches 1st end  |
| Hydrostatic Test Pressure:  |
| 6000.0 pounds per square inch   |
| Inside Surface Condition:   |

## NSN 4720-01-281-5898

Nonmetallic Hose Assembly - Page 2 of 2



| Measuring Method And Length:                    |
|---|
| 24.000 inches                                   |
| Special Features:                               |
| Inner conveying tube material-rubber, synthetic |
| Media For Which Designed:                       |
| Fuel/oil, hydrocarbon single response           |
| Thread Series Designator:                       |
| Un 1st end                                      |
| Shelf Life:                                     |
| N/a   |
| Unit Of Measure:                                |
|   |
| Demilitarization:                               |
|   |

No Fiig: A542a0