

View Online at <https://aerobasegroup.com/nsn/4720-01-281-7875>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.735 inches

**Minimum Inside Bending Radius:**

2.500 inches

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

10000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided fiber and 2nd layer braided fiber and outer layer molded polyurethane

**Maximum Operating Pressure:**

2500.0 pounds per square inch

**Thread Size:**

0.562 inches 2nd end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

5000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Oil resistant and ozone resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

28.000 inches

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0