Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-281-7879

| Cross Section | onal Shape: |
|----------------|---|
| Round | |
| Thread Clas | s: |
| 3b 1st end | |
| Thread Dire | ction: |
| Right-hand 1 | st end |
| Inside Diam | eter: |
| 0.688 inches | |
| Tempurature | e Rating: |
| -40.0 degree | s fahrenheit and 300.0 degrees fahrenheit single response |
| Outside Dia | meter: |
| 0.938 inches | |
| Minimum In: | side Bending Radius: |
| 4.500 inches | |
| End Applica | tion: |
| 1510-00-715 | -9379 |
| Connection | Style: |
| Swivel nut fla | are 1st end |
| End Connec | tion Design: |
| Straight 1st e | and |
| Connection | Туре: |
| Threaded int | ernal tube 1st end |
| Features Pro | ovided: |
| Reusable en | d fittings |
| Thready Qty | Per Inch (tpi): |
| 12 1st end | |
| Burst Test P | Pressure: |
| 3750.0 poun | ds per square inch |
| Layer Comp | osition And Location: |
| 1st layer brai | ded corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire |
| Maximum O | perating Pressure: |
| 1000.0 poun | ds per square inch |
| Thread Size | : |
| 1.062 inches | 1st end |
| Seat Angle: | |
| 37.0 degrees | s 1st end |
| Hydrostatic | Test Pressure: |
| 2000.0 poun | ds per square inch |
| Inside Surfa | ce Condition: |
| Smooth | |
| Measuring N | Nethod And Length: |
| 26.625 inche | S |



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0