Nonmetallic Hose Assembly - Page 1 of 2



etc.).

View Online at https://aerobasegroup.com/nsn/4720-01-281-7882

	Il Shape:
Round	
Thread Direction	n:
Right-hand 1st e	and
Inside Diamete	r:
0.188 inches	
Tempurature R	ating:
-40.0 degrees fa	hrenheit single response and 250.0 degrees fahrenheit single response
Outside Diame	ter:
0.516 inches	
Minimum Insid	e Bending Radius:
3.000 inches	
Hose Or Tubing	g Specification/std Data:
Sae j517, 100r5	, size 4-81343 standard (includes industry or association standards, individual manufactureer standards,
Connection Sty	rle:
Inverted flare 1s	t end
End Connectio	n Design:
Straight 1st end	
End Fitting Co	nponent And Material:
Complete fitting	steel all ends
Connection Ty	pe:
Threaded exterr	nal pipe 1st end
Features Provi	ded:
Reusable end fi	tings
Second End Re	elationship With First End:
Identical	
Burst Test Pres	ssure:
12000.0 pounds	per square inch
First End Swiv	el Action Capability:
Not included	
Layer Compos	ition And Location:
1st layer braided	d textile yarn err-100
Maximum Ope	ating Pressure:
3000.0 pounds	per square inch
Thread Size:	
0.250 inches 1s	t end
Seat Angle:	
30.0 degrees 1s	t end
Hydrostatic Te	st Pressure:
6000.0 pounds	per square inch
Vacuum In Tor	r:
50.8	

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition: Smooth Measuring Method And Length: 60.000 inches **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Nptf 1st end **Specification Data:** Sae j517, 100r5, size 4-81343 national std/spec Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A542a0