## NSN 4720-01-282-8498

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-282-8498

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.550 inches
Minimum Inside Bending Radius:
1.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
350.0 pounds per square inch
Layer Composition And Location:
Outer layer braided polyamide cord
Maximum Operating Pressure:
100.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
200.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Convoluted
Measuring Method And Length:
15.375 inches
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a

## NSN 4720-01-282-8498

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0