NSN 4720-01-283-4988

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-283-4988

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 3a 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.750 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.250 inches |
| Minimum Inside Bending Radius: |
| 9.500 inches |
| Connection Style: |
| External seat for gasket seal (boss) 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external boss 1st end |
| Features Provided: |
| Reusable end fittings |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Burst Test Pressure: |
| 9000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 2250.0 pounds per square inch |
| Thread Size: |
| 1.750 inches 1st end |
| Hydrostatic Test Pressure: |
| 4500.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 84.000 inches |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |

Un 1st end

NSN 4720-01-283-4988

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0