NSN 4720-01-283-9620



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-283-9620 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 2.080 inches **Minimum Inside Bending Radius:** 10.000 inches **Connection Style:** Compression 1st end **End Flange Construction:** Solid 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external tube 1st end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 600.0 pounds per square inch **Layer Composition And Location:** 1st layer spirally laid steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 150.0 pounds per square inch **Thread Size:** 1.875 inches 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 25.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:**

Un 1st end Shelf Life: N/a

NSN 4720-01-283-9620

Nonmetallic Hose Assembly - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A542a0