NSN 4720-01-284-2223

56.000 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-284-2223

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 1.125 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.500 inches |
| Minimum Inside Bending Radius: |
| 9.000 inches |
| End Application: |
| 3810-01-205-2716 |
| Connection Style: |
| Swivel nut, gasket seal 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Burst Test Pressure: |
| 2500.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric |
| Maximum Operating Pressure: |
| 625.0 pounds per square inch |
| Thread Size: |
| 1.688 inches 1st end |
| Hydrostatic Test Pressure: |
| 1250.0 pounds per square inch |
| Vacuum In Torr: |
| 254.0 |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |

NSN 4720-01-284-2223

Nonmetallic Hose Assembly - Page 2 of 2



| N | Λ | edia | For | Which | Design | ned: |
|---|---|------|-----|-------|--------|------|
| | | | | | | |

Air and fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0