## NSN 4720-01-284-6113

300.0 pounds per square inch

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-284-6113

Cross Sectional Shape:
Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Flange Thickness:
0.359 inches 2nd end
Outside Diameter:
2.080 inches
Minimum Inside Bending Radius:
10.000 inches
Exterior Color:
Black
Flange Outside Diameter:
2.437 inches 2nd end
Connection Style:
Plain swivel w/ gasket groove 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
600.0 pounds per square inch
Layer Composition And Location:
1st layer braided fiber and 2nd layer spiral interlocked steel and outer layer molded rubber, synthetic
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
1.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:

## NSN 4720-01-284-6113

Nonmetallic Hose Assembly - Page 2 of 2



## **Outer Covering Environmental Protection:** Abrasion resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 25.000 inches Flange Style: Round w/ out bolt holes 2nd end Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Un 1st end Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A542a0