

View Online at <https://aerobasegroup.com/nsn/4720-01-284-6907>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.406 inches

Temperature Rating:

-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

0.766 inches

Minimum Inside Bending Radius:

1.750 inches

Exterior Color:

Blue

End Application:

2320-01-123-1602

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

1st layer braided polyester cord and 2nd layer braided wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

38.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon and ethylene glycol and air single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A542a0